

WS Extensions

7.04 closefile()

Purpose

With `closefile()`, you can save the changes and close an opened file. After performing file operations like `open`, `read`, and `append`, we recommend you close the file to save the changes. Also, closing a file helps you to start reading it from the beginning while performing the read operation.

The `closefile()` returns a boolean value based on the close status of the file.

- **True:** If the file closed successfully
- **False:** If the file is not closed

Syntax

Format 1: The file name can be specified directly in the command if the file exists in your scripts directory.

```
closefile("Filename.ext");
```

Format 2: The file path needs to be specified if the file does not exist in your scripts directory.

```
// You need to place double backward slashes between the folder names  
in the file path.  
closefile("C:\\LiquidUI\\MMModule\\filename.ext");
```

Properties

- `Filename.ext` - Name of the file with extension

Options

The `closefile()` command does not take any options.

Example

In the following example, we will close the `ordertypes.txt` file after adding the specified names into it.

```
//Allows you to open the file internally to add the names into it.
```

WS Extensions

```
openfile("ordertypes.txt",{  
  "delimiter":",","output":true,"append":true});  
name1 = "Standard Order";  
name2 = "Promotion Order";  
name3 = "Returns";  
appendfile("ordertypes.txt",{ "name1":true,"name2":true,"name3":true});  
closefile("ordertypes.txt");
```

The file is now closed after completing the read or edit operation.

Tips and Tricks

- You need to open a file before performing edit or read operations and close the file to save the changes.
- SAP mode-specific file opening and closing are possible.

Usage Details

- [File operations using closefile\(\)](#)
- [File handling using closefile\(\)](#)
- [Logging Capability with closefile\(\)](#)
- [Attach VB script to SAP with closefile\(\)](#)
- [Increment counter using appendfile\(\) and closefile\(\)](#)
- [appendfile\(\) with closefile\(\)](#)

Unique solution ID: #1046

Author: Punil Shah

Last update: 2022-01-06 05:50